

---

# **Simple TMX Library Documentation**

***Release 1.8.1***

**Julian Marchant**

July 15, 2016



## CONTENTS

<b>1</b>	<b>tmx.TileMap</b>	<b>3</b>
<b>2</b>	<b>Other Classes</b>	<b>5</b>
<b>3</b>	<b>Functions</b>	<b>11</b>
<b>4</b>	<b>Indices and tables</b>	<b>13</b>
	<b>Python Module Index</b>	<b>15</b>
	<b>Index</b>	<b>17</b>



This library reads and writes the Tiled TMX format in a simple way. This is useful for map editors or generic level editors, and it's also useful for using a map editor or generic level editor like Tiled to edit your game's levels.

To load a TMX file, use `tmx.TileMap.load()`. You can then read the attributes of the returned `tmx.TileMap` object, modify the attributes to your liking, and save your changes with `tmx.TileMap.save()`. That's it! Simple, isn't it?

At the request of the developer of Tiled, this documentation does not explain in detail what each attribute means. For that, please see the TMX format specification, found here:

<http://doc.mapeditor.org/reference/tmx-map-format/>



---

**CHAPTER  
ONE**

---

## **TMX.TILEMAP**

**class tmx.TileMap**

This class loads, stores, and saves TMX files.

**version**

The TMX format version.

**orientation**

Map orientation. Can be “orthogonal”, “isometric”, “staggered”, or “hexagonal”.

**renderorder**

The order in which tiles are rendered. Can be "right-down", "right-up", "left-down", or "left-up". Default is "right-down".

**width**

The width of the map in tiles.

**height**

The height of the map in tiles.

**tilewidth**

The width of a tile.

**tileheight**

The height of a tile.

**staggeraxis**

Determines which axis is staggered. Can be “x” or “y”. Set to None to not set it. Only meaningful for staggered and hexagonal maps.

**staggerindex**

Determines what indexes along the staggered axis are shifted. Can be “even” or “odd”. Set to None to not set it. Only meaningful for staggered and hexagonal maps.

**hexsidelength**

Side length of the hexagon in hexagonal tiles. Set to None to not set it. Only meaningful for hexagonal maps.

**backgroundcolor**

The background color of the map as a hex string (e.g. "FF0000" or "#00FF00"), or None if no background color is defined.

**nextobjectid**

The next available ID for new objects. Set to None to not set it.

**properties**

A list of *Property* objects indicating the map’s properties.

**tilesets**

A list of `Tileset` objects indicating the map's tilesets.

**layers**

A list of `Layer`, `ObjectGroup`, and `ImageLayer` objects indicating the map's tile layers, object groups, and image layers, respectively. Those that appear in this list first are rendered first (i.e. furthest in the back).

**classmethod TileMap.load(*fname*)**

Load the TMX file with the indicated name and return a `TileMap` object representing it.

**TileMap.save(*fname*, *data\_encoding='base64'*, *data\_compression=True*)**

Save the object to the file with the indicated name.

Arguments:

- `data_encoding` – The encoding to use for layers. Can be "base64" or "csv". Set to None for the default encoding (currently "base64").
- `data_compression` – Whether or not compression should be used on layers if possible (currently only possible for base64-encoded data).

---

CHAPTER  
TWO

---

## OTHER CLASSES

**class tmx.Image** (*format\_=None, source=None, trans=None, width=None, height=None, data=None*)

**format**

Indicates the format of image data if embedded. Should be an extension like "png", "gif", "jpg", or "bmp". Set to None to not specify the format.

**source**

The location of the image file referenced. If set to None, the image data is embedded.

**trans**

The transparent color of the image as a hex string (e.g. "FF0000" or "#00FF00"), or None if no color is treated as transparent.

**width**

The width of the image in pixels; used for tile index correction when the image changes. If set to None, the image width is not explicitly specified.

**height**

The height of the image in pixels; used for tile index correction when the image changes. If set to None, the image height is not explicitly specified.

**data**

The image data if embedded, or None if an external image is referenced.

**class tmx.ImageLayer** (*name, offsetx, offsety, opacity=1, visible=True, properties=None, image=None*)

**name**

The name of the image layer.

**offsetx**

The x position of the image layer in pixels.

**offsety**

The y position of the image layer in pixels.

**opacity**

The opacity of the image layer as a value from 0 to 1.

**visible**

Whether or not the image layer is visible.

**properties**

A list of *Property* objects indicating the properties of the image layer.

**image**

An *Image* object indicating the image of the image layer.

```
class tmx.Layer (name, opacity=1, visible=True, offsetx=0, offsety=0, properties=None, tiles=None)
```

**name**

The name of the layer.

**opacity**

The opacity of the layer as a value from 0 to 1.

**visible**

Whether or not the layer is visible.

**offsetx**

Rendering offset for this layer in pixels.

**offsety**

Rendering offset for this layer in pixels.

**properties**

A list of *Property* objects indicating the properties of the layer.

**tiles**

A list of *LayerTile* objects indicating the tiles of the layer.

The coordinates of each tile is determined by the tile's index within this list. Exactly how the tiles are positioned is determined by the map orientation.

```
class tmx.LayerTile (gid, hflip=False, vflip=False, dflip=False)
```

**gid**

The global ID of the tile. A value of 0 indicates no tile at this position.

**hflip**

Whether or not the tile is flipped horizontally.

**vflip**

Whether or not the tile is flipped vertically.

**dflip**

Whether or not the tile is flipped diagonally (X and Y axis swapped).

```
class tmx.Object (name, type_, x, y, width=0, height=0, rotation=0, gid=None, visible=True, properties=None, ellipse=False, polygon=None, polyline=None, id_=None)
```

**id**

Unique ID of the object as a string if set, or `None` otherwise.

**name**

The name of the object. An arbitrary string.

**type**

The type of the object. An arbitrary string.

**x**

The x coordinate of the object in pixels. This is the left edge of the object in orthogonal orientation, and the center of the object otherwise.

**y**

The y coordinate of the object in pixels. This is the bottom edge of the object.

**width**

The width of the object in pixels.

**height**

The height of the object in pixels.

**rotation**

The rotation of the object in degrees clockwise.

**gid**

The tile to use as the object's image. Set to `None` for no reference to a tile.

**visible**

Whether or not the object is visible.

**properties**

A list of `Property` objects indicating the object's properties.

**ellipse**

Whether or not the object should be an ellipse.

**polygon**

A list of coordinate pair tuples relative to the object's position indicating the points of the object's representation as a polygon. Set to `None` to not represent the object as a polygon.

**polyline**

A list of coordinate pair tuples relative to the object's position indicating the points of the object's representation as a polyline. Set to `None` to not represent the object as a polyline.

```
class tmx.ObjectGroup(name, color=None, opacity=1, visible=True, offsetx=0, offsety=0, draworder=None, properties=None, objects=None)
```

**name**

The name of the object group.

**color**

The color used to display the objects in this group as a hex string (e.g. "FF0000" or "#00FF00"). Set to `None` for no color definition.

**opacity**

The opacity of the object group as a value from 0 to 1.

**visible**

Whether or not the object group is visible.

**offsetx**

Rendering offset for this layer in pixels.

**offsety**

Rendering offset for this layer in pixels.

**draworder**

Can be "topdown" or "index". Set to `None` to not define this.

**properties**

A list of `Property` objects indicating the object group's properties

**objects:**

A list of `Object` objects indicating the object group's objects.

```
class tmx.Property(name, value)
```

**name**

The name of the property.

**value**

The value of the property.

```
class tmx.TerrainType (name, tile, properties=None)
```

**name**

The name of the terrain type.

**tile**

The local tile ID of the tile that represents the terrain visually.

**properties**

A list of *Property* objects indicating the terrain type's properties.

```
class tmx.Tile (id_, terrain=None, probability=None, properties=None, image=None, animation=None)
```

**id**

The local tile ID within its tileset.

**terrain**

Defines the terrain type of each corner of the tile, given as comma-separated indexes in the list of terrain types in the order top-left, top-right, bottom-left, bottom-right. Leaving out a value means that corner has no terrain. Set to None for no terrain.

**probability**

A percentage indicating the probability that this tile is chosen when it competes with others while editing with the terrain tool. Set to None to not define this.

**properties**

A list of *Property* objects indicating the tile's properties.

**image**

An *Image* object indicating the tile's image. Set to None for no image.

**animation**

A list of *Frame* objects indicating this tile's animation. Set to None for no animation.

```
class tmx.Tileset (firstgid, name, tilewidth, tileheight, source=None, spacing=0, margin=0, xoffset=0, yoffset=0, tilecount=None, columns=None, properties=None, image=None, terrain-types=None, tiles=None)
```

**firstgid**

The first global tile ID of this tileset (this global ID maps to the first tile in this tileset).

**name**

The name of this tileset.

**tilewidth**

The (maximum) width of the tiles in this tileset.

**tileheight**

The (maximum) height of the tiles in this tileset.

**source**

The external TSX (Tile Set XML) file to store this tileset in. If set to None, this tileset is stored in the TMX file.

**spacing**

The spacing in pixels between the tiles in this tileset (applies to the tileset image).

**margin**

The margin around the tiles in this tileset (applies to the tileset image).

**xoffset**

The horizontal offset of the tileset in pixels (positive is right).

**yoffset**

The vertical offset of the tileset in pixels (positive is down).

**tilecount**

The number of tiles in this tileset. Set to `None` to not specify this.

**columns**

The number of tile columns in the tileset. Set to `None` to not specify this.

**properties**

A list of `Property` objects indicating the tileset's properties.

**image**

An `Image` object indicating the tileset's image. Set to `None` for no image.

**terraintypes**

A list of `TerrainType` objects indicating the tileset's terrain types.

**tiles**

A list of `Tile` objects indicating the tileset's tile properties.



---

CHAPTER  
THREE

---

## FUNCTIONS

`tmx.data_decode (data, encoding, compression=None)`

Decode encoded data and return a list of integers it represents.

This is a low-level function used internally by this library; you don't typically need to use it.

Arguments:

- `data` – The data to decode.
- `encoding` – The encoding of the data. Can be "base64" or "csv".
- `compression` – The compression method used. Valid compression methods are "gzip" and "zlib". Set to None for no compression.

`tmx.data_encode (data, encoding, compression=True)`

Encode a list of integers and return the encoded data.

This is a low-level function used internally by this library; you don't typically need to use it.

Arguments:

- `data` – The list of integers to encode.
- `encoding` – The encoding of the data. Can be "base64" or "csv".
- `compression` – Whether or not compression should be used if supported.



---

**CHAPTER  
FOUR**

---

**INDICES AND TABLES**

- genindex
- modindex
- search



PYTHON MODULE INDEX

t

tmx, 1



**A**

animation (tmx.Tile attribute), 8

**B**

backgroundcolor (tmx.TileMap attribute), 3

**C**

color (tmx.ObjectGroup attribute), 7

columns (tmx.Tileset attribute), 9

**D**

data (tmx.Image attribute), 5

data\_decode() (in module tmx), 11

data\_encode() (in module tmx), 11

dflip (tmx.LayerTile attribute), 6

draworder (tmx.ObjectGroup attribute), 7

**E**

ellipse (tmx.Object attribute), 7

**F**

firstgid (tmx.Tileset attribute), 8

format (tmx.Image attribute), 5

**G**

gid (tmx.LayerTile attribute), 6

gid (tmx.Object attribute), 7

**H**

height (tmx.Image attribute), 5

height (tmx.Object attribute), 6

height (tmx.TileMap attribute), 3

hexsidelength (tmx.TileMap attribute), 3

hflip (tmx.LayerTile attribute), 6

**I**

id (tmx.Object attribute), 6

id (tmx.Tile attribute), 8

Image (class in tmx), 5

image (tmx.ImageLayer attribute), 5

image (tmx.Tile attribute), 8

image (tmx.Tileset attribute), 9

ImageLayer (class in tmx), 5

**L**

Layer (class in tmx), 5

layers (tmx.TileMap attribute), 4

LayerTile (class in tmx), 6

load() (tmx.TileMap class method), 4

**M**

margin (tmx.Tileset attribute), 8

**N**

name (tmx.ImageLayer attribute), 5

name (tmx.Layer attribute), 6

name (tmx.Object attribute), 6

name (tmx.ObjectGroup attribute), 7

name (tmx.Property attribute), 7

name (tmx.TerrainType attribute), 8

name (tmx.Tileset attribute), 8

nextobjectid (tmx.TileMap attribute), 3

**O**

Object (class in tmx), 6

ObjectGroup (class in tmx), 7

offsetx (tmx.ImageLayer attribute), 5

offsetx (tmx.Layer attribute), 6

offsetx (tmx.ObjectGroup attribute), 7

offsety (tmx.ImageLayer attribute), 5

offsety (tmx.Layer attribute), 6

offsety (tmx.ObjectGroup attribute), 7

opacity (tmx.ImageLayer attribute), 5

opacity (tmx.Layer attribute), 6

opacity (tmx.ObjectGroup attribute), 7

orientation (tmx.TileMap attribute), 3

**P**

polygon (tmx.Object attribute), 7

polyline (tmx.Object attribute), 7

probability (tmx.Tile attribute), 8

properties (tmx.ImageLayer attribute), 5

properties (tmx.Layer attribute), 6

properties (tmx.Object attribute), [7](#)  
properties (tmx.ObjectGroup attribute), [7](#)  
properties (tmx.TerrainType attribute), [8](#)  
properties (tmx.Tile attribute), [8](#)  
properties (tmx.TileMap attribute), [3](#)  
properties (tmx.Tileset attribute), [9](#)  
Property (class in tmx), [7](#)

## R

renderorder (tmx.TileMap attribute), [3](#)  
rotation (tmx.Object attribute), [7](#)

## S

save() (tmx.TileMap method), [4](#)  
source (tmx.Image attribute), [5](#)  
source (tmx.Tileset attribute), [8](#)  
spacing (tmx.Tileset attribute), [8](#)  
staggeraxis (tmx.TileMap attribute), [3](#)  
staggerindex (tmx.TileMap attribute), [3](#)

## T

terrain (tmx.Tile attribute), [8](#)  
TerrainType (class in tmx), [8](#)  
terraintypes (tmx.Tileset attribute), [9](#)  
Tile (class in tmx), [8](#)  
tile (tmx.TerrainType attribute), [8](#)  
tilecount (tmx.Tileset attribute), [9](#)  
tileheight (tmx.TileMap attribute), [3](#)  
tileheight (tmx.Tileset attribute), [8](#)  
TileMap (class in tmx), [3](#)  
tiles (tmx.Layer attribute), [6](#)  
tiles (tmx.Tileset attribute), [9](#)  
Tileset (class in tmx), [8](#)  
tilesets (tmx.TileMap attribute), [3](#)  
tilewidth (tmx.TileMap attribute), [3](#)  
tilewidth (tmx.Tileset attribute), [8](#)  
tmx (module), [1](#)  
trans (tmx.Image attribute), [5](#)  
type (tmx.Object attribute), [6](#)

## V

value (tmx.Property attribute), [7](#)  
version (tmx.TileMap attribute), [3](#)  
vflip (tmx.LayerTile attribute), [6](#)  
visible (tmx.ImageLayer attribute), [5](#)  
visible (tmx.Layer attribute), [6](#)  
visible (tmx.Object attribute), [7](#)  
visible (tmx.ObjectGroup attribute), [7](#)

## W

width (tmx.Image attribute), [5](#)  
width (tmx.Object attribute), [6](#)  
width (tmx.TileMap attribute), [3](#)

## X

x (tmx.Object attribute), [6](#)  
xoffset (tmx.Tileset attribute), [9](#)

## Y

y (tmx.Object attribute), [6](#)  
yoffset (tmx.Tileset attribute), [9](#)